UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/002,185	12/05/2001	Colin D. Nayler	95-525	3474

20736   7590   08/05/2005

MANELLI DENISON & SELTER
2000 M STREET NW SUITE 700
WASHINGTON, DC 20036-3307

EXAMINER
TORRES, JUAN A

ART UNIT	PAPER NUMBER
2631	

DATE MAILED: 08/05/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)	
Office Action Summary	10/002,185	NAYLER, COLIN D.	
	Examiner	Art Unit	
	Juan A. Torres	2631	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE _3_ MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on _30 June 2005_.

2a)☒ This action is **FINAL**.   2b)☐ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) _1-13_ is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) _1-13_ is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☒ The drawing(s) filed on _30 June 2005_ is/are: a)☒ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All   b)☐ Some * c)☐ None of:

        1.☐ Certified copies of the priority documents have been received.

        2.☐ Certified copies of the priority documents have been received in Application No. _____.

        3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____.

5) ☐ Notice of Informal Patent Application (PTO-152)

6) ☐ Other: _____.

DETAILED ACTION

Drawings

The modifications to the drawings were received on 06/30/2005. These

modifications are accepted by the Examiner.

Response to Arguments

Applicant's arguments filed on 06/30/2005 have been fully considered but they

are not persuasive.

As per claims 1 and 6:

The Applicant contends, "Each of the independent claims 1 and 6 specify an

arrangement for supplying equalizer settings to a digital-feedforward equalizer. In

particular, each of the independent claims specify: (1) supplying a prescribed initial set

of equalizer settings to the digital feedforward equalizer, (2) comparing the equalized

signal samples relative to a prescribed equalization threshold. and (3) selectively

changing the supplied equalizer settings, based on the comparing step, until the

equalized signal samples reach the prescribed equalization threshold....Hence, use of a

digital feedforward equalizer enables rapid convergence based on the independent

initialization by selectively changing the supplied equalizer settings until the prescribed

equalization is reached, while minimizing the introduction of instability due to unsettled

data (see, e.g., page 5, line 31 to page 6, line 3 of the specification). The use of a

digital-feedforward equalizer, plus the selective changing of the supplied equalizer

settings until the equalized signal samples reach the prescribed equalization threshold,

is neither disclosed nor suggested in the applied prior art. Lo describes an equalization

technique that relies on a closed loop system using a phase locked loop (PLL) (see, e.g., Abstract at lines 10-13', col. 2, lines 30-34; col. 3, lines 16-24). In particular, Lo relies on a PLL 34 to identify a timing correlation of an edge of an equalized signal relative to a recovered clock signal (RCLK).".

The Examiner disagrees and asserts, that, as indicated in the previous Office Action, what lo discloses is an apparatus and method for determining an optimum equalizer setting for a signal equalizer in a communication network receiver (title of the patent); and an optimum equalizer setting is determined for a signal equalizer in a network receiver by successively setting the equalizer to different predetermined settings.. (abstract).

The Applicant contends, "Lo further describes that the optimum equalizer setting is chosen based on determining the relative edge distribution for each equalizer setting, and identifying the corresponding relative edge distribution that demonstrates the minimum distribution of jitter (i.e., based resembling the distribution curve 46 of Fig. 4A, see col. 4, lines 47-50).... As apparent from the foregoing, Lo provides no disclosure whatsoever of the claimed "digital feedforward equalizer", as claimed. Nor does Lo provide any suggestion of any digital feedforward equalizer, since Lo relies on using a PLL in a closed loop system to determine the minimum jitter. For this reason alone, the rejection should be withdrawn because it fails to demonstrate that Lo discloses each and every element of the claim"

The Examiner disagrees and asserts, that, it is very well known that an equalizer is an adaptive filter that try to adapt the response of the channel to reduce (ideally to

remove) the ISI (Inter Symbol Interference). The use of terms like feedforward equalizer

is more relate to DFEs (Decision Feedback equalizer) because in this structure there

are two equalizers and one way the differentiate them is to call FFE (feedforward

equalizer) to the equalizer that is in the path of the signal and FBE (feedback equalizer

to the equalizer that is not in the path of the signal). If only one equalizer is used,

usually doesn't need to have an identifier. The equalizer used by Lo is the same

function an location that the equalizer disclosed by the present application, it is in the

path of the signal, the fact that he doesn't call feedforward doesn't make any difference

because has the same function. An equalizer is an adaptive filter that changes its

coefficients adaptively. There are several documents and US Patents that support this

view that have been included in this Office Action including:

a) Yu (US 5517527 A) that clearly shows that the equalizer disclosed in the

reference is a feedforward equalizer (figure 3) that in this particular case he call it

feedforward filter, that by the way it is his real function. The structure presented in this

US patent is very similar to the architecture disclosed by the applicant including the

adaptation of the filters (feedforward and feedback) using the error detector (also called

noise detector, because the slicer (threshold detector) error will provide the noise in the

signal.

b) He (US 6870881 B1) that in the same way discloses a FFE (feedforward

Equalizer with the same structure that the Applicant and Yu. In this case he called the

adaptive filter FFE (figure 7)

c) Chadha (US 6876699 B1) also discloses (figure 4 column 13 lines 50-58) the same architecture and in this case, and he also called FFE (Feedforward equalizer).

All these references are used for illustrative purposes only, and are not used as a base of the rejections.

The Applicant contends, "Further, as demonstrated above, Lo does not disclose or suggest the claimed selectively changing the supplied equalizer settings, based on the comparing step, until the equalized signal samples reach the prescribed equalization threshold." Rather, Lo requires each and every equalizer setting to be evaluated to determine the minimum jitter, and hence describes necessarily changing the supplied equalizer settings. Claims 1 and 6, however, specify "selectively changing", thereby permitting the possibility that the claimed prescribed initial set of equalizer settings may be used, without further modification, based on the prescribed initial set generating equalized signal samples that reach the prescribed equalization threshold. For this reason alone the 102 rejection should be withdrawn.".

The Examiner disagrees and asserts, that, Lo teaches selectively changing the equalizer settings, as indicated in the previous Office Action, Lo discloses a method in a physical layer transceiver coupled to a prescribed network medium having an undetermined length, the method comprising: supplying a prescribed initial set of equalizer settings to a digital feedforward equalizer, the digital feedforward equalizer configured for outputting equalized signal samples based on equalizing received signal samples, having encountered inter-symbol interference by transmission via the prescribed network medium, according to supplied equalizer settings (figure 1 column 2

lines 45-47); comparing the equalized signal samples relative to a prescribed

equalization threshold (figure 2 column 6 lines 1-4); and selectively changing the

supplied equalizer settings, based on the comparing step, until the equalized signal

samples reach the prescribed equalization threshold (column 7 lines 30-31).

The Applicant contends, "Applicant traverses the reference to column 6, lines 1-4

as teaching the claimed "prescribed equalization threshold" -- the cited portion

describes a signal detection signal that identifies whether a cable is connected to the

receiver: (T)he equalizer 32 also outputs a reset signal and a detection signal (SIG-

DET), which may be used by the equalizer 36 to detect an initialization condition in the

equalizer controller 32, **for example** a reset state or a disconnect state. (Col. 4, lines 1-

5). As shown in FIG. 5, the state machine includes a link down state 72, executed by

the equalizer controller 36 in response to reception of either a reset signal or

deassertion of the signal detect signal (SIG-DET), indicating no signal is present on the

medium 14. (Col. 5, lines 33-37). The equalizer controller 36 remains the link down

state 72 until reception of the detection signal (SIG-DET). The detection signal SEG-

DET (sic) is a logical signal output by the equalizer 32 that indicates that signal

transitions are occurring above a defined threshold, for example when a cable L is

connected to the receiver 30. (Col. 5, line 66 to col. 6, line 4). Hence, the "threshold" in

Lo refers to a basic signal threshold to indicate that the a cable is connected to the

receiver, and not the claimed "prescribed equalization threshold". Anticipation cannot be

established based on a piecemeal application of the reference, where the Examiner

picks and chooses isolated features of the reference in an attempt to synthesize the

claimed invention. Anticipation requires the presence in a single prior art reference

disclosure of each and every element of the claimed invention, arranged as in the claim.

For these and other reasons, the 102 rejection of independent claims 1 and 6 should be

withdrawn.

The Examiner strongly disagrees and asserts, that, Lo teaches selectively

changing the equalizer settings, as indicated in the previous Office Action, Lo discloses

a method in a physical layer transceiver coupled to a prescribed network medium

having an undetermined length, the method comprising: supplying a prescribed initial

set of equalizer settings to a digital feedforward equalizer, the digital feedforward

equalizer configured for outputting equalized signal samples based on equalizing

received signal samples, having encountered inter-symbol interference by transmission

via the prescribed network medium, according to supplied equalizer settings (figure 1

column 2 lines 45-47 "The method includes setting the signal equalizer to one of a

plurality of predetermined equalizer settings"); comparing the equalized signal samples

relative to a prescribed equalization threshold (figure 2 column 6 lines 1-4 The detection

signal SEG.sub.-- DET is a logical signal output by the equalizer 32 that indicates that

signal transitions are occurring above a defined threshold); and selectively changing the

supplied equalizer settings, based on the comparing step, until the equalized signal

samples reach the prescribed equalization threshold (column 7 lines 30-31 "an optimum

equalizer setting is determined for a signal equalizer by successively setting the

equalizer to different predetermined settings, and determining the normalized

distribution result for each of the predetermined equalizer settings").

The use of feedforward equalizers in the way claimed is very well known. In the previous Office Acton the Examiner indicated prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Yu (US 5517527) discloses an adaptive equalizer to be implemented in a receiver to cancel the ISI with a decision feedback equalizer structure including a feedforward filter and a feedback filter. Werner (US 6069917) discloses a decision feedback equalizer (DFE) with a feed-forward filter and a feedback filter using blind training of the DFE is performed using a statistical-based tap updating algorithm for the feed-forward filter, and a symbol-based type of tap updating algorithm for the feedback filter. Kuenast (US 5027369) discloses a rapid convergence decision feedback equalizer; the DFE has two separate portions which each function as an individual DFE having a different number of taps and different adaptive tap sizes; a first DFE portion operates alone to rapidly converge the measured error to a predetermined threshold; a control circuit is used to determine when the threshold is reached and to activate the second DFE portion for rapid further error convergence. Gelfand (US 6144697) discloses equalization techniques to reduce intersymbol interference.

In addition in this Office Action the Examiner recommends the reading of Becker (US 3292110 patented in 1962) "transversal equalizer for digital transmission systems, wherein polarity of time-spaced portions of output signal controls corresponding multiplier setting" that also discloses all the features of the present invention; also "The digital signal processing handbook" by Vijay Madisetti & Douglas Wiliams, section VI" Adaptive Filtering" chapters 18-24; "Adaptive Filtering Algorithms and practical

implementation" by Ramirez Diniz; and "Principles of Digital Transmission with wireless

applications" chapter 8 pp 380-426 by Sergio Benedetto.

For these reasons and the reason stated in the previous Office Action, the

rejection of claims 1 and 6 are maintained.

As per claims 4-5 and 9:

The Applicant contends, "The rejection of claims 4-5 and 9 is further traversed.

Lo provides no reference whatsoever to any "absolute value", let alone the claimed

location where a statistically substantial number of the data values representing a

symbol absolute value of "1" should occur for an equalized signal. As described above,

Lo relies on identifying timing relationships between a equalized signal edge 40 and an

edge 44 of the recovered clock. Column 6 of Lo describes identifying whether the timing

relationship for each signal edge 40 falls within one of the distribution regions 48, 50,

52, 54, used to identify jitter.".

The Examiner disagrees and asserts, that, as indicated in the previous Office

Action, Lo discloses a counter configured for determining, within the count interval, a

first number of the equalized signal samples having an absolute value that exceeds a

first reference level occurs for an equalized signal (figure 5 block 76 column 6 lines 24-

32 "The equalizer controller 36 exits the blind wait state 74 and enters a count transition

state 76 in order to determine the normalized distribution result for each of the

predetermined equalizer settings. Specifically, the count transition state 76 counts the

number of signal transitions on the incoming data signal. The total number of transitions

is counted using the "transition_count" state variable, and the number of transitions of

the outside segments 48 and/or 54 are counted using the "outside_count" (OC) state

variable. Hence, if any digital code (SEG) representing any correlation result is received

from the digital PLL 34, the count transitions state 76 increments the transition count.").

Obviously a counter that is set to 1 and is incremented, it value and it absolute

value is the same, because its value is always positive.

For these reasons and the reason stated in the previous Office Action, the

rejection of claims 4-5 and 9 are maintained.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that

form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-9 are rejected under 35 U.S.C. 102(b) as being anticipated by Lo (US

6097767).

As per claim 1 Lo discloses a method in a physical layer transceiver coupled to a

prescribed network medium having an undetermined length, the method comprising:

supplying a prescribed initial set of equalizer settings to a digital feedforward equalizer,

the digital feedforward equalizer configured for outputting equalized signal samples

based on equalizing received signal samples, having encountered inter-symbol

interference by transmission via the prescribed network medium, according to supplied

equalizer settings (figure 1 column 2 lines 45-47); comparing the equalized signal

samples relative to a prescribed equalization threshold (figure 2 column 6 lines 1-4);

and selectively changing the supplied equalizer settings, based on the comparing step,

until the equalized signal samples reach the prescribed equalization threshold (column

7 lines 30-31).

As per claim 2 Lo discloses claim 1. Lo also discloses supplying the prescribed

initial set of equalizer settings based on a predetermined characterization of the

prescribed network medium at a prescribed length (figure 1 column lines 34-39 and

figure 5 column 5 lines 23-27).

As per claim 3 Lo discloses claim 2. Lo also discloses selectively changing step

includes successively supplying groups of equalizer settings based on the

predetermined characterizations of the prescribed network medium at successively

changing lengths (figure 2 column 1 lines 34-39 and column 7 lines 28-40).

As per claim 4 Lo discloses claim 3. Lo also disclose selectively changing step

includes successively generating a count interval representing reception of a

statistically-based prescribed number of signal samples (column 6 lines 21-24); first

determining, within the count interval, a first number of the equalized signal samples

having an absolute value that exceeds a first reference level occurs for an equalized

signal (column 6 lines 24-43); and second determining whether the first number reaches

the prescribed equalization threshold, the prescribed equalization threshold

representing an expected number of detected signal samples that exceed the first

reference level within the count interval (column 6 lines 44-57).

As per claim 5 Lo discloses claim 1. Lo also disclose selectively changing step

includes successively generating a count interval representing reception of a

statistically-based prescribed number of signal samples (column 6 lines 21-24); first

determining, within the count interval, a first number of the equalized signal samples

having an absolute value that exceeds a first reference level occurs for an equalized

signal (column 6 lines 24-43) ; and second determining whether the first number

reaches the prescribed equalization threshold, the prescribed equalization threshold

representing an expected number of detected signal samples that exceed the first

reference level within the count interval (column 6 lines 44-57).

As per claim 6 Lo discloses a physical layer transceiver configured for retrieving

signal samples from a prescribed network medium having an undetermined length, the

physical layer transceiver comprising: a digital feedforward equalizer configured for

generating equalized signal samples from the retrieved signal samples and based on

supplied equalizer settings, the retrieved signal samples having encountered

intersymbol interference by transmission via the prescribed network medium (figures 1

and 2 blocks 16 and 32 column 1 line 23-32 and column); and an equalizer controller

configured for supplying the supplied equalizer settings to the digital feedforward

equalizer, the equalizer controller configured for supplying a prescribed initial set of

equalizer settlings and comparing the equalized signal samples, having been generated

based on the initial set of equalizer settings, relative to a prescribed equalization

threshold, the equalizer controller configured for selectively changing the supplied

equalizer settings until the equalized signal samples reach the prescribed equalization

threshold (figure 2 block 36 column 4 lines 61-64).

As per claim 7 Lo discloses claim 6. Lo also discloses that the equalizer

controller includes a coefficients generator configured for outputting the prescribed initial

set of equalizer settings and the selectively changed equalizer settings based on a

predetermined characterization of the prescribed network medium at respective

prescribed lengths (figure 1 column lines 34-39 and figure 5 column 5 lines 23-27).

As per claim 8 Lo discloses claim 7. Lo also discloses that the equalizer

controller further comprises a controller state machine configured for asserting an initial

signal at initialization of the digital feedforward equalizer and a change signal based on

a comparison result between the equalized signal samples and the prescribed

equalization threshold, the coefficients generator configured for outputting a

corresponding group of equalizer settings representing a successively changing

network medium length in response to each corresponding assertion of the change

signal (figure 5 column 5 lines 23-27 and column 7 lines 28-40).

As per claim 9 Lo discloses claim 8. Lo also discloses that the equalizer

controller further comprises: a timer configured for generating a count interval

representing reception of a statistically-based prescribed number of signal samples

(figure 5 block 74 column 6 lines 5-12); a counter configured for determining, within the

count interval, a first number of the equalized signal samples having an absolute value

that exceeds a first reference level occurs for an equalized signal (figure 5 block 76

column 6 lines 24-32); and a comparator configured for outputting an equalization status

signal based on whether the first number reaches the prescribed equalization threshold,

the prescribed equalization threshold representing an expected number of detected

signal samples that have an absolute value exceeding the first reference level within the

count interval, the controller state machine selectively asserting the change signal

based on the equalization status signal (figure 5 block 78 column lines 44-57).

As per claim 10 Lo discloses claim 1. Lo also discloses that the prescribed

equalization threshold represents an expected number of detected signal samples

having been detected within a prescribed count interval and having an absolute value

exceeding a reference level (column 6 lines 24-43).

As per claim 11 Lo discloses claim 10. Lo also discloses that the reference level

identifies a prescribed minimum value necessary for an ideal equalized signal sample to

be detected as a prescribed data value (column 6 lines 44-57)

As per claim 12 Lo discloses claim 6. Lo also discloses that the prescribed

equalization threshold represents an expected number of detected signal samples

having been detected within a prescribed count interval and having an absolute value

exceeding a reference level (column 6 lines 24-43).

As per claim 13 Lo discloses claim 12. Lo also discloses that the reference level

identifies a prescribed minimum value necessary for an ideal equalized signal sample to

be detected as a prescribed data value (column 6 lines 44-57)

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in

this Office action. Accordingly, **THIS ACTION IS MADE FINAL.** See MPEP

§ 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37

CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within

TWO MONTHS of the mailing date of this final action and the advisory action is not

mailed until after the end of the THREE-MONTH shortened statutory period, then the

shortened statutory period will expire on the date the advisory action is mailed, and any

extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of

the advisory action. In no event, however, will the statutory period for reply expire later

than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Juan A. Torres whose telephone number is (571) 272-

3119. The examiner can normally be reached on Monday-Friday 9:00 AM - 5:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Mohammad H. Ghayour can be reached on (571) 272-3021. The fax phone

number for the organization where this application or proceeding is assigned is 703-

872-9306.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free).

Juan Alberto Torres, Ph. D.
07-14-2005

KEVIN BURD
PRIMARY EXAMINER